

	Outline Vinduer A/S Fabriksvej 4 9640 Farsø, Danmark 2023
Facadeelementer – Beregnet til bygninger/ Facade elements – Intended for buildings Facadevinduer og døre i træ aluminium Daylight 2 lags/ Facade windows and doors wood aluminium Daylight 2 layer	
DoP ref. ID CE 23.3-8 EN 14351-1:2006 + A2:2016	
Termisk transmissionskoefficient (U-værdi)/ Thermal transmittance coefficient (U-value)	
1- fags oplukkeligt vindue/ Single window	
1230 x 1480 mm med standard rude/ 1230 x 1480 mm with standard pane:	1,29*
Rammedør/ Frame door	
1230 x 2180 mm med standard rude/ 1230 x 2180 mm with standard pane:	1,23*
Strålingsegenskaber/ Radiation properties	
Standardrudens solfaktor (g-værdi)/ Standard pane's sun factor (g-value)	0,53
Standardrudens lystransmission (Lt-værdi)/ Standard pane's light transmittance (Lt-value)	0,74
Andre ydeevnebestemmelser/ Other performance measures	
Sikkerhedsudstyrs bæreevne (topvendevindue)/ Load-bearing capacity of safety equipment (top hung window)	Bestået/ Passed
Vindlast/ Wind load	NPD
Vandtæthed/ Watertightness	NPD
Akustisk ydeevne/ Acoustic performance	NPD
<i>NPD: no performance determined (ingen ydeevne fastlagt)</i>	

*Aktuelle termiske transmissionskoefficient (U-værdi) oplyses ved henvendelse til Outline Vinduer A/S

jf. EN 14351-1:2006 + A2:2016, Tabel E.1 note c. /

Current thermal transmission coefficient (U-value) can be obtained from Outline Vinduer A/S in accordance to EN 14351-1:2006 + A2:2016, Table E.1 note c.