

	Outline Vinduer A/S Fabriksvej 4 9640 Farsø, Danmark  2023
Facadeelementer – Beregnet til bygninger/ Facade elements – Intended for buildings Vinduer og døre i træ aluminium 2 lags/ Wood/ aluminium windows and doors 2 layer	
DoP ref. ID CE 23.6-4 EN 14351-1:2006 + A2:2016	
<b>Termisk transmissionskoefficient (U-værdi)/          Thermal transmittance coefficient (U-value)</b>	
1- fags oplukkeligt vindue/ Single window	
1230 x 1480 mm med standard rude/ 1230 x 1480 mm with standard pane:	1,34*
Rammedør/ Frame door	
1230 x 2180 mm med standard rude/ 1230 x 2180 mm with standard pane:	1,35*
<b>Strålingsegenskaber/ Radiation properties</b>	
Standardrudens solfaktor (g-værdi)/ Standard pane's sun factor (g-value)	0,73
Standardrudens lystransmission (Lt-værdi)/ Standard pane's light transmittance (Lt-value)	0,82
<b>Andre ydeevnebestemmelser/ Other performance measures</b>	
Sikkerhedsudstyrs bæreevne (topvendevindue)/ Load-bearing capacity of safety equipment (top hung window)	Bestået/ Passed
Vindlast/ Wind load	NPD
Vandtæthed/ Watertightness	NPD
Akustisk ydeevne/ Acoustic performance	NPD
<i>NPD: no performance determined (ingen ydeevne fastlagt)</i>	

\*Aktuelle termiske transmissionskoefficient (U-værdi) oplyses ved henvendelse til Outline Vinduer A/S

jf. EN 14351-1:2006 + A2:2016, Tabel E.1 note c. /

Current thermal transmission coefficient (U-value) can be obtained from Outline Vinduer A/S in accordance to EN 14351-1:2006 + A2:2016, Table E.1 note c.