

	Outline Vinduer A/S Fabriksvej 4 9640 Farsø, Danmark 2023
Facadeelementer – Beregnet til bygninger/ Facade elements – Intended for buildings Facadevinduer og døre i fyrretræ 3 lags / Pinewood facade windows and doors 3 layer	
DoP ref. ID CE 23.3-3 EN 14351-1:2006 + A2:2016	
Termisk transmissionskoefficient (U-værdi)/ Thermal transmittance coefficient (U-value) 1- fags oplukkeligt vindue/ Single window 1230 x 1480 mm med standard rude/ 1230 x 1480 mm with standard pane: 0,91* Rammedør/ Frame door 1230 x 2180 mm med standard rude/ 1230 x 2180 mm with standard pane: 0,96*	
Strålingsegenskaber/ Radiation properties Standardrudens solfaktor (g-værdi)/ Standard pane's sun factor (g-value) 0,57 Standardrudens lystransmission (Lt-værdi)/ Standard pane's light transmittance (Lt-value) 0,74	
Andre ydeevnebestemmelser/ Other performance measures Sikkerhedsudstyrs bæreevne (topvendevindue)/ Load-bearing capacity of safety equipment (top hung window) Bestået/ Passed Vindlast/ Wind load NPD Vandtæthed/ Watertightness NPD Akustisk ydeevne/ Acoustic performance NPD	
NPD: no performance determined (ingen ydeevne fastlagt)	

*Aktuelle termiske transmissionskoefficient (U-værdi) oplyses ved
henvendelse til Outline Vinduer A/S

jf. EN 14351-1:2006 + A2:2016, Tabel E.1 note c. /

Current thermal transmission coefficient (U-value) can be obtained from
Outline Vinduer A/S in accordance to EN 14351-1:2006 + A2:2016, Table
E.1 note c.